5

10

20

25

## What is claimed is:

- 1. A high frequency crystal oscillator increasing levels of higher harmonic components against a level of a fundamental frequency of a generating circuit using a quartz-crystal element, selecting any higher harmonic component by a surface acoustic wave filter, amplifying the selected higher harmonic component, and obtaining a high frequency oscillation output signal, wherein
- a piezo-electric substrate that composes the surface acoustic wave filter is a crystal substrate.
- 2. A high frequency crystal oscillator, comprising:
  - a crystal oscillating unit causing a center voltage of an oscillation output signal to be higher than the center voltage of a power supply voltage so as to distort an output signal and output the output signal; and
  - a surface acoustic wave filter extracting a particular frequency component of the output signal of the crystal oscillating unit, a piezo-electric substrate of the surface acoustic wave filter being a crystal substrate.

3. A high frequency crystal oscillator, comprising:

an oscillating unit using a quartz-crystal
5 element;

an amplifying unit amplifying higher harmonic components of an output signal of the oscillating unit; and

a surface acoustic wave filter selectively

outputting a particular frequency higher harmonic
component of an output signal amplified by the
amplifying unit, a piezo-electric substrate of the
surface acoustic wave filter being a crystal
substrate.

15

20

4. The high frequency crystal oscillator as set forth in claim 3, wherein

the amplifying unit amplifies the higher harmonic component of the output signal using a saturation region of input and output characteristics thereof.

- 5. A high frequency crystal oscillator, comprising:
- 25 crystal oscillating means for causing a center

voltage of an oscillation output signal to be higher than the center voltage of a power supply voltage so as to distort an output signal and output the output signal; and

surface acoustic wave filter means for extracting a particular frequency component of the output signal of the crystal oscillating means, a piezo-electric substrate of the surface acoustic wave filter means being a crystal substrate.

10

20

6. A high frequency crystal oscillator, comprising:

oscillating means for using a quartz-crystal element;

amplifying means for amplifying higher harmonic components of an output signal of the oscillating means; and

surface acoustic wave filter means selectively outputting а particular frequency higher harmonic component of an output amplified by the amplifying means, a piezo-electric substrate of the surface acoustic wave filter being a crystal substrate.

7. A high frequency signal oscillating method,

## comprising:

distorting an output signal of an oscillating circuit using a crystal oscillator and outputting the output signal; and

extracting a particular frequency component from the output signal by supplying the output signal to a surface acoustic wave filter having a piezo-electric substrate that is a crystal substrate.

10

15

5

8. A high frequency signal oscillating method, comprising the steps of:

amplifying higher harmonic components of an output signal of an oscillating unit using a quartz-crystal element; and

extracting a particular frequency component from the output signal by supplying the amplified output signal to a surface acoustic wave filter having a piezo-electric substrate that is a crystal

20 substrate .